

CHRYSO® Fluid Optima 256 EMX

High Range Water Reducing Admixture

DESCRIPTION

New generation of High Range Water Reducing Admixture based on proprietary polymer. Specially designed for highly technical ReadyMix concrete, CHRYSO Fluid Optima 256 EMx provides extended slump retention and pumpability to achieve targeted concrete quality and performance on-site. CHRYSO Fluid Optima 256 EMx improves concrete robustness to optimize the mix design cost/performance ratio.

Meets or exceeds the requirements of ASTM C-494 Type A & F



BENEFITS

- High Early and Ultimate Strength Performance
- Reduces Job Site Water Additions
- Improved Flowability
- Allows better utilization of mixes incorporating high volumes of pozzolans such as fly ash
- High SCM usage contributes to the protection of our environment (Reduction of CO₂ emissions encouraged by LEED directives)

FIELDS OF APPLICATION

- All Cement Types
- Precast Concrete, Ready Mix Concrete
- Post Tensioned and Prestressed Concrete
- Self Consolidating Concrete (SCC)
- Very High Early Strength Concrete, High SCM Replacement
- Segmental Retaining Wall (SRW)

METHOD OF USE

Dosage

- The recommended dosage rate for CHRYSO Fluid Optima 256 EMx is 2 to 7 oz/cwt (130 to 457 ml/100 kg) of cementitious material for a Type A and 5 to 16 oz/cwt (326 to 1045 ml/100 kg) of cementitious material for a Type F.
- CHRYSO Fluid Optima 256 EMx can be added with the initial water or, for optimum performance, on the wetted concrete. It should not be added with or on the dry cement.
- Dosage rates may vary when used in conjunction with other CHRYSO admixtures.
- Trial mixes should be conducted to determine the dosage rate needed.
- Because local job conditions vary, please contact your local CHRYSO sales representative for further assistance if using the product outside the recommended dosage ranges.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.com

CHRYSO Inc. - 3958 Ruger Dr • Royse City • TX 75189 & PO Box 190 • Rockwall • TX 75087 Tél.: +1 (972) 772 6010

P.1/2

CHRYSO® Fluid Optima 256 EMX

High Range Water Reducing Admixture

INDICATIVE INFORMATION

Product Nature	Liquid
Color	Green
Lifetime	12 months
Cl⁻ Ions content	< 0,100 %
Specific gravity	1,090
pH	4,50

This product does not contain any purposely added calcium chloride or other chloride based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

Packaging :

- Drum 215L
- IBC 1000L
- Bulk

PRECAUTIONS

- CHRYSO® Fluid Optima 256 EMx should be stored at or above 40°F (5°C). If frozen, thaw and agitate thoroughly to return to its normal state before use.
- Do not use pressurized air for agitation.
- CHRYSO® Fluid Optima 256 EMx is compatible with most CHRYSO admixtures if they are added separately to the concrete mix.
- However, it is not recommended for use in concrete containing naphthalene-based admixtures including ProPel AG, or melamine-based admixtures.

SAFETY

Prior to any use, please read carefully the Material Safety Data Sheets.

The information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be conducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.com

CHRYSO Inc. - 3958 Ruger Dr • Royse City • TX 75189 & PO Box 190 • Rockwall • TX 75087 Tél.:+1 (972) 772 6010