

**CHRYSO® EnviroMix® 350**Full Range Water Reducing Admixtures  
High SCM Replacement**DESCRIPTION**

High-Performance Admixture based on CHRYSO® EnviroMix® technology, specially designed for high SCM concrete mix designs. CHRYSO® EnviroMix® 350 provides high early strengths to increase SCM content in concrete and achieve substantial savings. It provides optimized workability and placeability to achieve targeted concrete quality and performance on-site while reducing jobsite time and costs.

**Meets or exceeds the requirements of ASTM C-494 Type A and F**

**ADVANTAGES**

- Allows better utilization of mixes incorporating high volumes of pozzolans such as fly ash
- Provides uniform, normal-setting characteristics
- Proprietary finishing aid improves workability and finishability
- High SCM usage contributes to the protection of our environment (Reduction of CO<sub>2</sub> emissions encouraged by LEED directives)
- Improves Cementitious Material Performance (More PSI/lb)

**FIELDS OF APPLICATION**

- All Cement Types
- Ready Mix Concrete
- Manufactured Sand
- High SCM Replacement
- Concrete Paving

**METHOD OF USE****Dosage**

- The recommended dosage rate for CHRYSO® EnviroMix® 350 is 3 to 10 oz/cwt (195 to 652 ml/100 kg) of cementitious material for a Type A and 8 to 18 oz/cwt (522 to 1174 ml/100 kg) of cementitious material for a Type F.
- CHRYSO® EnviroMix® 350 can be added with the initial water or, for optimum performance, on the wetted concrete. It should not be added with or on the dry cement.
- Dosage rates may vary when used in conjunction with other CHRYSO admixtures.
- Trial mixes should be conducted to determine the dosage rate needed.
- Because local job conditions vary, please contact your local CHRYSO sales representative for further assistance if using the product outside the recommended dosage ranges.

The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. [www.chryso.com](http://www.chryso.com)

CHRYSO Inc. - 3958 Ruger Dr • Royse City • TX 75189 & PO Box 190 • Rockwall • TX 75087 Tél.:+1 (972) 772 6010

# CHRYSO® EnviroMix® 350

Full Range Water Reducing Admixtures  
High SCM Replacement

## CHARACTERISTICS

<b>Product Nature</b>	Liquid
<b>Color</b>	Amber
<b>Shelf life</b>	12 months
<b>Cl<sup>-</sup> Ions content</b>	< 0.100
<b>Specific gravity (25°C) in g/ml</b>	1.030
<b>pH (25°C)</b>	4.00

This product does not contain any purposely added calcium chloride or other chloride based components. It will not promote or contribute to corrosion of reinforcing steel in concrete.

### Packaging :

- 55 gallon drum (210 L)
- 264 gallon tote (1000 L)
- Bulk

## PRECAUTIONS

- CHRYSO® EnviroMix® 350 should be stored at or above 34°F (1°C). If frozen, thaw and agitate thoroughly to return to its normal state before use.
- Do not use pressurized air for agitation.
- CHRYSO® EnviroMix® 350 is compatible with most CHRYSO admixtures if they are added separately to the concrete mix.
- However, it is not recommended for use in concrete containing naphthalene-based admixtures including ProPel AG, or melamine-based admixtures.

## SAFETY

Prior to any use, please read carefully the Safety data Sheet.

The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. [www.chryso.com](http://www.chryso.com)

CHRYSO Inc. - 3958 Ruger Dr • Royse City • TX 75189 & PO Box 190 • Rockwall • TX 75087 Tél.:+1 (972) 772 6010