

## TECHNICAL DATA SHEET

Chryso  
Concrete  
Solutions

03/03/2026

# Chryso®Pave 148 SE

Water Repelling and Efflorescence Reducing  
Admixture

### DESCRIPTION

CHRYSO®Pave 148 SE is a pore-blocking Admixture based on polymeric proven technology, specifically designed for pavers. CHRYSO®Pave 148 SE provides long-lasting resistance to water penetration without significantly modifying the hardened properties of drycast or ready mix concrete.

**Meets or exceeds the requirements of ASTM C-494 Type S and E-514**

### ADVANTAGES

- Superior Primary and Secondary Efflorescence Control
- Exceeds ASTM E-514 requirements
- Reduced Permeability and Absorption
- Does Not Affect Air Content of Fresh Concrete
- Improves Concrete Chemical Resistance and Durability

### FIELDS OF APPLICATION

- All Cement Types
- Concrete Pavers
- Dry Cast Concrete
- Machine Manufactured Concrete
- Permeability and Adsorption Reduction

### Method of Use

#### Dosage

- The recommended dosage rate for CHRYSO®Pave 148 SE is 4 to 23 oz/cwt (260 to 1495 ml/100 kg) of cementitious material for a Type S.
- CHRYSO®Pave 148 SE should be added to the wetted concrete with at least 75% of the total water. It should not be added with or on the dry cement. An additional 90 seconds of mixing is required after the addition of the CHRYSO®Pave 148 SE.
- Because local job conditions vary, please contact your local CHRYSO sales representative for further assistance if using the product outside the recommended dosage ranges.

### CHARACTERISTICS

Product Nature	Liquid
Color	White
Apparent density	0,990

### PRECAUTIONS

- CHRYSO®Pave 148 SE should be stored at or above 34°F (1°C). If frozen, thaw and agitate thoroughly to return to its normal state before use.
- Do not use pressurized air for agitation.

The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. [www.chryso.com](http://www.chryso.com)

CHRYSO Inc. - 12770 Merit Drive Suite 750, Dallas, TX 75251 USA Tel.:+1 (972) 772 6010

P.1/2

## TECHNICAL DATA SHEET

# Chryso® Pave 148 SE

Water Repelling and Efflorescence Reducing Admixture

Chryso  
Concrete  
Solutions

03/03/2026

pH (25°C)

9,50

### PACKAGING

- 210 L (55 Gallons) Drum
- 1000L Tote (275 gallons)
- Bulk

- CHRYSO®Pave 148 SE is compatible with most CHRYSO admixtures if they are added separately to the concrete mix. However, it is not recommended for use in concrete containing naphthalene-based admixtures including ProPel AG, or melamine-based admixtures.

### SAFETY

Prior to any use, please read carefully the Safety Data Sheet.

The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the "Application" paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. [www.chryso.com](http://www.chryso.com)

CHRYSO Inc. - 12770 Merit Drive Suite 750, Dallas, TX 75251 USA Tel.:+1 (972) 772 6010

P.2/2